

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 October 2005 (06.10.2005)


PCT

(10) International Publication Number
WO 2005/091712 A2

- (51) International Patent Classification: **Not classified**
- (21) International Application Number:
PCT/TB2005/000737
- (22) International Filing Date: 22 March 2005 (22.03.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/554,989 22 March 2004 (22.03.2004) US
- (71) Applicant (for all designated States except US): **VETCO AIBEL AS** [NO/NO]; Bergerveien 12, P.O. BOX 81, N-1375 Billingstad (NO).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **HOEN, Christopher** [NO/NO]; Christopher Hoen, Levretoppen 56, N-1346 Gjettem (NO).
- (74) Common Representative: **VETCO AIBEL AS**; c/o Henrik Fransson AB, Forskargränd 8, B 194, S-72226 Västerås (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: A METHOD AND A DEVICE FOR MONITORING AND/OR CONTROLLING A LOAD ON A TENSIONED ELONGATED ELEMENT



(57) Abstract: The invention relates to a method for monitoring and/or controlling a load on a slender, tensioned elongated element extending from a subsea wellhead element to a surface vessel, by which the tensioned elongated element is arranged so as to be displaced in its longitudinal direction into or out of the subsea wellhead element via an entry at a top end of the latter. The method comprises the steps of: - measuring the structural behaviour of the wellhead element, and - estimating the bending moment and/or declination of the tensioned elongated element in a bottom region adjacent to and/or at said entry upon basis of the measurement of the structural behaviour of the wellhead element. The invention also relates to a corresponding device.



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*